

Torque screwdriver, 0.4-2.0 Nm, 9 x 0.4 Nm x 0.8 Nm x 1.2 Nm x 1.6 Nm x 2.0 Nm x 192 mm



VDE-insulated torque screwdriver handle with 9 mm hexagon socket; exclusively for Wera Kraftform Kompakt VDE interchangeable blades. For professional screwing/fine adjustment AND for torque-controlled screwing. Non-slip, non-overtightening torque function for right/left-hand tightening. With five selectable tightening torques right/left (0.4; 0.8; 1.2; 1.6; 2.0 Nm), which can be set extremely quickly. One fixed position (torque lock) for unlimited loosening/tightening torques. With freewheel sleeve for good guidance of the tool during the screwdriving process.

- VDE torque hand tool 7508 with 5 preset values (0.4; 0.8; 1.2; 1.6; 2.0 Nm)
- Speed: Extremely fast setting of the tightening torques
- Safe: Torque function for right/left-hand tightening that cannot be overtightened
- Torque lock function: For high loosening and tightening torques without torque
- With freewheel sleeve and holder for Wera VDE interchangeable blades

Item no.	WL90439
Model	7508 VDE Kraftform Safe-Torque Speed
Manufacturer	WERA
Manufacturer article no.	05075870001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	199 mm
Width	66 mm
Height	36 mm
Length with packaging	199 mm
Width with packaging	66 mm

Products for the electronic industry



Height with packaging	36 mm
Sales unit	1 piece
Content unit	1 piece
Incl. battery	no
VDE	yes
ESD compliant	no
Torque	0.4 – 2 Nm