

## Electronic slotted screwdriver, 0.16 x 0.8 x 40 mm



High-quality Wera Micro screwdriver for precision mechanical screwdriving. Lightning-fast twisting is possible by resting the hand on the rotating cap and thanks to the fast-twisting zone underneath the rotating cap. No more time-consuming regripping. Power zone with integrated soft zones ensures the transmission of high loosening and tightening torques. Precision zone for the correct angle of rotation for adjustment work. The Wera Black Point tip offers a precise fit and optimized corrosion protection. Take it easy tool finder with color coding according to profiles and size stamping - for finding the required tool quickly and easily.

- Kraftform Micro screwdriver for slotted screws
- Multi-component Kraftform Micro handle for fast and ergonomic screwdriving
- With roll-off protection and rotating cap for fast twirling
- The Wera Black Point tip offers a precise fit and optimized corrosion protection
- With Take it easy tool finder: color coding according to profiles and size stamping

<b>Item no.</b>	<b>WL90659</b>
Model	2035
Manufacturer	WERA
Manufacturer article no.	05117990001
GPSR manufacturer data	WERA Werkzeuge GmbH Korzelter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Length	137 mm
Width	13 mm
Height	13 mm
Length with packaging	174 mm
Width with packaging	64 mm
Height with packaging	34 mm
Sales unit	1 piece
Content unit	1 piece

Products for the electronic industry



VDE	no
ESD compliant	no
Blade length	40 mm
Blade width	0.8 mm
Blade thickness	0.16 mm

## Other versions

Item no.	Blade length	Blade width	Blade thickness
<b>WL90659</b>	<b>40 mm</b>	<b>0.8 mm</b>	<b>0.16 mm</b>
WL90660	40 mm	1 mm	0.18 mm
WL90661	40 mm	1.2 mm	0.2 mm
WL90666	40 mm	1.2 mm	0.25 mm
WL90667	40 mm	1.5 mm	0.23 mm
WL90662	40 mm	1.8 mm	0.3 mm
WL90670	40 mm	2 mm	0.4 mm
WL90665	40 mm	2.5 mm	0.35 mm
WL90675	50 mm	2 mm	0.3 mm
WL90663	50 mm	2.5 mm	0.4 mm
WL90664	50 mm	3 mm	0.5 mm
WL90668	60 mm	1.5 mm	0.23 mm
WL90669	60 mm	1.8 mm	0.3 mm
WL34550	60 mm	2 mm	0.4 mm
WL90672	80 mm	2.5 mm	0.4 mm
WL73902	80 mm	3 mm	0.5 mm
WL90673	80 mm	3.5 mm	0.6 mm
WL90674	80 mm	4 mm	0.8 mm
WL90671	100 mm	2 mm	0.4 mm