

## Ultrasonic bath with overflow pocket and heating, 40 kHz, 400 V, 135 l

---



Ultrasonic cleaning bath for professional applications - robust, powerful, modular: The ultrasonic cleaning bath with integrated heating is designed for use in industry, service and maintenance. The highly stable oscillating tank is made of stainless steel 1.4404 with a material thickness of 2 mm and welded connections - ideal for maximum durability even with intensive use. The modular design allows flexible configurations: from a single cleaning trough to complete, multi-stage cleaning lines. An integrated overflow pocket enables the connection of an oil separator, which reliably separates cleaned oil films from the cleaning solution. A spray pipe guides floating oil into the overflow pocket. Additional safety is provided by a fill level switch as dry-running protection for the heater and ultrasonic generator as well as height-adjustable feet. Suitable baskets, lids and coordinated cleaning and disinfectant concentrates are available as accessories to ensure efficient, thorough and gentle ultrasonic cleaning. Ideal for users who require high cleaning performance, reliability and flexibility.

- Particularly durable due to welded oscillating tank
- Simple operation
- With spray tube and overflow pocket
- Can be modularly combined to form a cleaning line
- Working capacity: 110 liters
- Volume to overflow: 125 liters
- Fill level marking: 350
- Thickness of the ultrasonic tank: 2.0 mm
- Shape of the tank corners: rectangular
- Inlet: 3-way ball valve G 1 incl. hose and hose nozzles, on the left side; brass, electroplated
- Outlet: 3-way ball valve G 1 incl. hose and hose nozzles, brass - electroplated, on the left-hand side
- Overflow: G 1 ball valve incl. hose nozzle, welded in, brass - electroplated, on the right-hand side
- Overflow pocket on the right-hand side
- Spray pipe on the left-hand side
- Tray base: straight
- Power setting: fixed
- Operation: rotary handle
- Time settings (min): 1 - 15, continuous operation
- Temperature range (adjustable): 30 - 80 °C
- Mains cable: 3 m, fixed to the appliance; with CEKON 16 three-phase plug
- Operating voltage: 400 V $\sim$ 3NPE 50/60 Hz
- Degree of protection (housing): IP 32
- Handles on the sides
- CE conformity: Low Voltage Directive 2014 / 35 / EU, EMC Directive 2014 / 30 / EU, RoHS Directive 2011 / 65 / EU

<b>Item no.</b>	<b>WL92019</b>
Manufacturer	SONOREX
Manufacturer article no.	8230
GPSR manufacturer data	BANDELIN electronic Heinrichstrasse 3-4 DE-12207 Berlin www.bandelin.com
Length	780 mm
Width	550 mm
Height	800 mm
Length with packaging	1150 mm
Width with packaging	800 mm

Height with packaging	1100 mm
Sales unit	1 piece
Content unit	1 piece
Shape	rectangular
Contents (liters)	135 l
Inner length	600 mm
Inner width	450 mm
Inner depth	450 mm
Material	Stainless steel
Incl. battery	no
Volume (liters)	135 l
Heating power	4800 W
Rated power	1000 W
Power cable	3 m
Voltage	400 V
Ultrasonic power (max.)	4000 W
Ultrasound frequency	40 kHz