

## RAKO-II-ESD Container 400x300x145 mm



The RAKO ESD Euro container from Utz is electrically conductive and can be moved manually using two shell handles. This makes this plastic container versatile and suitable for use in many industries. The ESD container measures 400 x 300 x 145 mm. Surface resistivity in accordance with DIN EN IEC 61340-5-3 is  $\geq 1 \times 10^4 \Omega$  and  $< 1 \times 10^{11} \Omega$ .

• Electrostatic Discharge•: Stackable•: Ergonomic•: Robust•: Sustainable•: Recyclable

Item no.	WL93732
Alternative article name	1070000
Manufacturer	UTZ
Manufacturer article no.	3-4313N-0.EL.9210
GPSR manufacturer data	Georg Utz GmbH Nordring 67 DE-48465 Schüttdorf www.utzgroup.de
Scope of delivery	1x RAKO-II container 400x300x145 mm, ESD
Sales unit	1 piece

Products for the electronic industry



Content unit	1 piece
Colour	black
ESD standard	61340-5-3
Outer length	400 mm
Outer width	300 mm
Outer height	145 mm
Inner length	363 mm
Inner width	263 mm
Inner height	130 mm
Incl. battery	no
Load capacity	25 kg
Volume (liters)	12 l
Packaging properties	dissipative
Compatible for cleanroom	no
Typical surface resistance (Rpp)	$\geq 1 \times 10^4 \Omega$ und $< 1 \times 10^{11} \Omega$
Material storage boxes	ESD PP
Clear height	130 mm
Stack Height	130 mm
Incl. lid	no
ESD compliant	yes