

Chip TOOL



The ERSA chip tool has been designed with ergonomics and precision in mind. With a large selection of SMD soldering tips, SMD chips from size 0201 to medium-sized PLCC can be removed safely and quickly.

The chip tool is supplied with the heat-optimized 0452MDLF tips. All 2-pin SMDs with side contacting can be processed quickly and efficiently with this mold. Anti-twist protection is also provided as standard. All tips for the SMD soldering and desoldering tweezers can be fitted with an alignment ring (E045600). This has a dowel pin that is inserted into a hole in the heat sink. If further soldering tips are planned, we recommend equipping them with the anti-twist protection. This saves time when changing tips. Each chip tool is supplied with the necessary Allen key. This is located at the head of the piston.

The SMD soldering and desoldering tweezers can be set to a maximum and minimum opening width to exactly match the component dimensions. This optimizes handling, especially when large quantities need to be processed. The fingers, hand and arm tire much more slowly.

The different shapes and dimensions of the soldering tips require an additional setpoint adjustment of the desired working temperature. For this purpose, the Digital 2000 A control station (0DIG203A) allows an identification number to be selected in the setup, which is set on the basis of a tip table. With a control unit from the i-CONxV (0IC113V 0IC223) or i-CON VARIO series (0ICV203A 0ICV203AP 0ICV403A), a plain text selection based on the article number is available.

- Pincette à dessouder CHIP tool pour i-CON, i-CON2 et DIGITAL 2000 A respectivement avec pincette à dessouder 40 ou le CHIP tool, SMT UNIT 60 A/AS, MICRO-CON 60 iA, DIGITAL 2000 A respectivement avec pincette à dessouder 40 ou le CHIP tool , Rework 80 et SMD 8000 respectivement avec pincette à dessouder TC40
- Largeur embout à dessouder 2 mm

Numéro d'article

WL22471

Products for the electronic industry



Modèle	450MDJ
Fabricant	ERSA
Numéro d'article du fabricant	0450MDJ
Données du fabricant du GPSR	ERSA GmbH Leonhard-Karl-Strasse 24 DE-97877 Wertheim www.ersa.de
Longueur avec emballage	345 mm
Largeur avec emballage	70 mm
Hauteur avec emballage	45 mm
Unité de vente	1 pièce
Unité de contenu	1 pièce
Conforme RoHS	oui
Puissance de chauffage	130 W
Puissance nominale	40 W
Tension	24 V
Temps de chauffage	50 s
Pièce à main (type)	fer à dessouder
Support assorti	0A43
Conseils de correspondance	0452, 0422
Unité de commande correspondante	0IC113V, 0IC113V0C, 0IC223V, 0IC22300C, 0ICV203A, 0ICV203AP, 0ICV203HP, 0ICV403A
Conforme aux normes ESD	oui