

Panne à souder de la série SxP, en forme de fer à cheval coudé, 0,5 x 15,21 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The SFP-series are nominally 390 °C. Metcal recommends the SFP-series for the majority of applications. However, the family also offer a higher temperature series designated SCP, nominally 450 °C, for high temperature and thermally demanding applications. STP-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- pour la plupart des demandes standard

N° d'article

WL24733

Products for the electronic industry



mannequin	SFP-DRH05
Fabricant	OKI
Fabricant Numéro d'article	SFP-DRH05
Informations sur le fabricant du GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unité de vente	1 pièce
Unité de contenu	1 pièce
ligne de produits	Série SxP
Température max.	421 °C
Série de panne à souder	SxP
longueur de pic	15,21 mm
largeur de pic	0,5 mm
forme de pic	coudé, ongulaire
alignement de pointe	coudé
Température de pointe	421 °C
pièce à main assortie	MFR-H1-SC
Conforme aux normes ESD	non

Autres versions

N° d'article	Température max.
WL27536	366 °C
WL24733	421 °C
WL27537	471 °C