

Panne à souder de la série SxV, en forme de burin, 2,5 x 11 mm



SxV-Solder Tips are the standard soldering tip range for the Metcal PS-900/MFR1100, MFR-2210, MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The temperature series SFV are nominally 390 °C. Metcal recommends the SFV-series for the majority of applications. However, the family also offer a higher temperature serie designated SCV, nominally 450 °C, for high temperature and thermally demanding applications. STV-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- pour la plupart des demandes standard
- convient aux pièces à main des systèmes PS et MFR

N° d'article

WL24779

Products for the electronic industry



mannequin	SFV-CH25
Fabricant	OKI
Fabricant Numéro d'article	SFV-CH25
Informations sur le fabricant du GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unité de vente	1 pièce
Unité de contenu	1 pièce
ligne de produits	Série SxV
Température max.	421 °C
Série de panne à souder	SxV
longueur de pic	11 mm
largeur de pic	2,5 mm
forme de pic	en forme de burin
alignement de pointe	droit
Température de pointe	421 °C
Conforme aux normes ESD	non

Autres versions

N° d'article	Température max.
WL27831	366 °C
WL24779	421 °C
WL26530	471 °C