

## Tube d'alimentation de rechange pour AL 2500 / AL-2A

The replacement feed tube for AL 2500 / AL-2A with a diameter of 0.8 mm is the ideal solution for precise soldering work. Developed for use with 0.8 mm solder wire, it ensures reliable and even feeding of the wire. This accessory is specially designed to meet the requirements of the AL 2500 and AL-2A models and supports efficient soldering technology. Perfect for professional applications, it offers a durable and robust design that can withstand the demands of intensive use. Discover the benefits of this high-quality spare part at [Weidinger.eu](http://Weidinger.eu).

Pour fil à souder D = 0,8 mm

|                               |                                                                                                                         |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Numéro d'article              | WL27192                                                                                                                 |
| Modèle                        | 0005159                                                                                                                 |
| Fabricant                     | JBC                                                                                                                     |
| Numéro d'article du fabricant | 0005159                                                                                                                 |
| Données du fabricant du GPSR  | JBC Soldering SL<br>Ramón y Cajal 3<br>ES-08750 Molins De Rei<br><a href="http://www.jbctools.com">www.jbctools.com</a> |
| Unité de vente                | 1 pièce                                                                                                                 |
| Unité de contenu              | 1 pièce                                                                                                                 |
| Diamètre                      | 0,8 mm                                                                                                                  |
| Conforme aux normes ESD       | oui                                                                                                                     |

### Autres versions

| Numéro d'article | Diamètre      |
|------------------|---------------|
| WL27191          | 0,5 mm        |
| <b>WL27192</b>   | <b>0,8 mm</b> |
| WL27193          | 1 mm          |
| WL27194          | 1,5 mm        |