Panne à souder de la série SxV, en forme de burin, 1 x 11 mm



SxV-Solder Tips are the standard soldering tip range for the Metcal PS-900/MFR1100, MFR-2210, MFR-1351-series soldering systems. The temperature/series is designated by the first digit following the dash in the part number. The SFV-series are nominally 390 ˚C. Metcal recommends the SFV-series for the majority of applications. However, thefamily also offer a higher temperature serie designated SCV, nominally 450 ˚C, for high temperature and thermally demanding applications. STV-series are nominally 330 ˚C for light load application. Can be used with leaded and lead-free solder The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- pour les applications sensibles à la température
- convient aux pièces à main des systèmes PS et MFR

Numéro d'article	**WL27820**

Modèle	STV-CH10
Fabricant	OKI
Numéro d'article du fabricant	STV-CH10
Données du fabricant du GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unité de vente	1 pièce
Unité de contenu	1 pièce
Série de produits	Série SxV
Température (max.)	366 °C
Série de conseils	SxV
Longueur de la pointe	11 mm
Largeur de la pointe	1 mm
Forme de la pointe	en forme de burin
Alignement des pointes	droit
Température de la pointe	365 °C
Conforme aux normes ESD	non

Autres versions

Numéro d'article	Température (max.)
WL27820	**366 °C**
WL24777	421 °C
WL27821	471 °C