

## Station de soudage à deux canaux 230 Volts 2 fers à souder MX-H1-AV

---



---

The MX-5200 Soldering, Desoldering, and Rework Series has increased power and process control, with dual-simultaneous ports for two users or a single user with dual applications. The MX-5200 can be operated with two handpieces dynamically sharing the 80-watt output power based on demand, adding even more application flexibility and speed. A built-in Net Power Meter displays a graphical and numerical representation of the power applied to the cartridge. User Programmable Power Save Mode: the time to enter Power Save Mode is adjustable from 10 to 120 minutes. Ground Fault Interrupt: AC ground monitor detects power line ground failures and immediately alerts the operator and shuts down the system. Universal Power Supply: automatically senses the input line voltage and adjusts accordingly, which allows for worldwide operation without adaptors or a change in performance. Full compatibility with existing and previous MX upgrade kits, tip-cartridges, handpieces, and accessories.

**FAST TIME-TO-RECOVERY:**

Delivers increased production rates and throughput no matter the application. The MX-5200 super-charged power supply seamlessly tackles the challenges of high-mass components, multilayered boards, and lead-free solders.

**SMARTHEAT® PROCESS CONTROL:**

The technology built into every Metcal SmartHeat® system means that soldering and rework are always performed at safe, controlled temperatures. Metcal users know that moderate fixed temperatures, where power is varied, provide the best assurance for a well-controlled soldering and rework process.

- 125 watts
- Tension d'entrée : 100 à 240 VAC

<b>Numéro d'article</b>	<b>WL27988</b>
Modèle	MX-5211
Fabricant	METCAL
Numéro d'article du fabricant	MX-5211
Données du fabricant du GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.metcal.com
Contenu de la livraison	Unité d'approvisionnement MX-PS5200 2 fers à souder MX-H1-AV 2 étagères MX-W1AV (avec abaissement de la température)
Unité de vente	1 pièce
Unité de contenu	1 pièce
Pouvoir	125 W
Tension	240 V
Station (type)	station de dessoudage, station de soudage
Température ambiante	10 – 40 °C
Conforme aux normes ESD	non