

## Chaussure Business ESD pour homme, noir, 42



At ATLAS®, only the best quality cowhides are processed. An extremely careful selection process ensures that only flawless, high-quality and soft leathers are used.

Whether you're wearing a classic suit or an urban business look, the models in the City Style series always go perfectly with your outfit. The City Style sole system brings together the latest technologies and the individual requirements of every wearer, whether on hard industrial floors or on the chic office parquet. The outsole system is light, flexible and particularly comfortable - be inspired by the models of the City Style series!

The anatomically shaped steel toe cap protects the foot in the toe area against impact of min. 200 joules and a compressive stress of min. 15 kN, according to EN ISO 20345:2012.

Particularly in everyday working life, with high physical stress, temperature-regulating properties are not only required, but expected. The aktiv-X functional lining stands for the highest quality, innovative technology and offers the wearer permanent, active moisture

---

Products for the electronic industry



regulation. The aktiv-X functional lining regulates moisture and ensures that the shoes dry again quickly. It does not stain, is skin-friendly and abrasion-resistant.

Work healthier with the right cushioning. The new 3D cushioning system from ATLAS® enables noticeably gentle and fatigue-free walking. The basis for this outstanding walking comfort is formed by three basic components: Pressure relief. Cushioning. Dynamics. This is ensured by the perfect interaction of a pressure-relieving insole and the light and responsive MPU sole technology.

geeignet für die Einlagenversorgung-DGUV 112-191

ATLAS® offers you a wide range of different orthopaedic insoles. The articles marked here are suitable for orthopaedic insoles according to DGUV regulation 112-191. The marking on the shoe is decisive for this.

- EN ISO 20345 S2 SRC
- ESD (résistance de fuite <35 Megaohms)
- convient pour l'alimentation en inserts (DGUV 112-191/BGR 191)
- largeur standard W10

|  |   |
|--|---|
| <b>N° d'article</b>                      | WL29172   |
| mannequin                                | CX 320 ESD  |
| Ligne de modèle                          | CX 320 ESD  |
| Fabricant                                | ATLAS   |
| Fabricant Numéro d'article               | 43700-42  |
| Informations sur le fabricant du GPSR    | ATLAS-Schuhfabrik GmbH & Co.KG<br>Frische Luft 159<br>DE-44319 Dortmund<br>www.atlasschuhe.de |
| Longueur avec emballage                  | 350 mm  |
| Largeur avec emballage                   | 250 mm  |
| Hauteur avec emballage                   | 150 mm  |
| Unité de vente                           | 1 paire   |
| Unité de contenu                         | 1 paire   |
| spécification de la couleur du fabricant | black   |
| Couleur                                  | noir  |
| concret                                  | soft cowhide  |
| Capuchon de protection                   | oui   |
| Chaussures d'exécution                   | chaussure basse   |
| Classification de sécurité               | S2  |

#### Products for the electronic industry



|                                   |   |
|-----------------------------------|---|
| Semelle de chaussure              | MPU sole technology   |
| Résistance au glissement          | SRC   |
| Largeur de la chaussure           | W10 (largeur standard)  |
| Chaussures d'équipement           | <ul style="list-style-type: none"><li>rembourrage fonctionnel aktiv-X</li><li>Renfort acier</li><li>technologie de semelles MPU®</li><li>cuir vachette pleine fleur</li></ul> |
| Matériaux Chaussures              | cuir de vachette souple   |
| Pointure EU                       | 42  |
| Conforme aux normes ESD           | oui   |
| Catégories à risques (décret PSA) | Catégorie 2   |

## Autres versions

| N° d'article   | Pointure EU |
|----------------|-------------|
| WL41691        | 39          |
| WL29166        | 40          |
| WL29167        | 41          |
| <b>WL29172</b> | <b>42</b>   |
| WL29168        | 43          |
| WL29173        | 44          |
| WL29174        | 45          |
| WL29175        | 46          |
| WL36003        | 47          |
| WL41693        | 48          |