

Unité d'alimentation à 1 outils - numérique, modulaire



The JBC DI-2D supply unit is a state-of-the-art 1-channel soldering station characterized by its compact design and advanced technology. With an output of 130W and a temperature range of 90°C to 450°C, it is ideal for precise soldering work in electronics production and repair.

The DI-2D has a digital LCD display that provides an accurate temperature reading. Thanks to the intelligent heat management with sleep and standby functions, the service life of the soldering tips is extended and energy consumption is reduced. The microprocessor-controlled unit allows individual configuration of all operating parameters, which can be secured by a PIN if required.

The DI-2D is ESD-safe and thus guarantees the protection of sensitive electronic components against electrostatic discharge. It is compatible with all JBC tools, including the DR560 and DS360 desoldering irons, the latter requiring an additional suction device such as the MS-A or MV-A.

With its compact size of 90×105×180mm and a weight of approx. 2.15kg, the DI-2D can be easily integrated into various working environments. The USB interface enables easy

connection to the PC for monitoring and controlling the soldering processes.

- Prise pour pompe à vide électrique / à air comprimé ou pour unité de commande N²
- Plus de 20 paramètres peuvent être enregistrés pour le soudage

Numéro d'article	WL30351
Modèle	DI-2D
Fabricant	JBC
Numéro d'article du fabricant	DI-2D
Données du fabricant du GPSR	JBC Soldering SL Ramón y Cajal 3 ES-08750 Molins De Rei www.jbctools.com
Longueur	180 mm
Largeur	90 mm
Hauteur	105 mm
Longueur avec emballage	220 mm
Largeur avec emballage	213 mm
Hauteur avec emballage	160 mm
Contenu de la livraison	1 DI-2D control unit
Unité de vente	1 pièce
Unité de contenu	1 pièce
Batterie incluse	non
Pouvoir	130 W
Tension	230 V
Fusible	1 A
Tension	230 V
Plage de température °C	90 – 450 °C
Puissance de sortie (max.) par canal	130 W
Ports de communication	USB interface station-PC
Résistance crête à terre	<2 ohms
Température ambiante	10 – 40 °C
Nombre de canaux	1
Conforme aux normes ESD	oui