Panne à dessouder D-intérieur 2,40mm (0,095")



The T80DT007 D-inner 2.40 mm desoldering tip from the T desoldering tip series from THERMALTRONICS has been developed for precise desoldering of larger solder joints. Its straight, conical tip enables controlled solder pick-up so that even larger soldering areas can be desoldered efficiently and cleanly.

The tip is RoHS compliant and lead-free, making it both environmentally friendly and safe for professional use. With a tip length of 13 mm and a tip width of 2.40 mm, it offers sufficient contact surface to reliably pick up solder without affecting adjacent components.

The desoldering tip is compatible with the DS-GUN-2 handpiece and suitable for the TMT-5000S-1 and TMT-5000S-2 soldering stations. The T-series guarantees consistently reliable desoldering results thanks to its precise design.

The 2.40 mm T80DT007 D-inside desoldering tip from THERMALTRONICS is the ideal choice for electronics engineers who want to desolder larger solder joints in a controlled, efficient and clean manner.
- Pour : TMT-5000S-1, TMT-5000S-2
- Série de pointes à souder T
- Conforme RoHS / sans plomb
- Type de pointe : Dessoudage

Numéro d'article	**WL38384**
Modèle	T80DT007
Fabricant	THERMALTRONICS
Numéro d'article du fabricant	T80DT007
Données du fabricant du GPSR	Thermaltronics Castle Peak Road. 489491 HKG-999077 Sham Shui Po www.thermaltronics.com
Longueur avec emballage	175 mm
Largeur avec emballage	19 mm

Hauteur avec emballage	19 mm
Longueur avec emballage en pouces	6,9 in
Largeur avec emballage en pouces	0,7 in
Hauteur avec emballage en pouces	0,7 in
Unité de vente	1 pièce
Unité de contenu	1 pièce
Série de produits	Série de pannes à dessouder T, 420°C - 475°C
Plage de température °C	420 – 475 °C
pointe à souder ou à dessouder	conseil pour dessouder
Série de conseils	Série T
Longueur de la pointe	13 mm
Longueur de la pointe en pouces	0,51 in
Largeur de la pointe	2,4 mm
Largeur de la pointe en pouces	0,09 in
Forme de la pointe	conique
Alignement des pointes	droit
Pièce à main assortie	DS-GUN-2
Conforme aux normes ESD	non