

Appareil de découpe/gaufrage/cintrage 1,3



Cutting, stamping and bending device for axial components
manual operation

- D wire up to 1.3 mm
- Delivery form: loose/belted
- manual operation
- up to 2,500 components/h
- Compressed air operation 4-6 bar with foot switch
- Weight: approx. 8 kg
- Dimensions: 300 x 500 x 210 mm
- Min. grid: 12.5 mm
- Max. grid: 70 mm

Operating mode:

- In order to enable axially wired components to be assembled quickly, they must be cut to the appropriate length and bent to the required grid before being inserted into the circuit board
- The setting is displayed on the relevant device scale
- The embossing for the connection pins is specific to the tool, and is implemented

according to customer requirements

- The device can be retrofitted for the various tools.
- The component is inserted manually between the tools
- These are then actuated by means of a pneumatic foot switch
- The changeover for different cutting and grid dimensions takes less than a minute (without tool)

Numéro d'article	WL38659
Modèle	C 042 S
Fabricant	BURST & ZICK
Numéro d'article du fabricant	C 042 S
Données du fabricant du GPSR	BURST & ZICK GmbH An der Roßweid 8 DE-76229 Karlsruhe www.burst-und-zick.de
Unité de vente	1 pièce
Unité de contenu	1 pièce
Batterie incluse	non