

Mini nettoyeur haute pression



Mini high-pressure cleaner

- Effective removal of persistent marks with "scouring agent jets"
- A mixture of conventional scouring agent and water can be processed in a ratio of approx. 1/2 to 1/5 in the built-in, fully swivelling tank
- Dust-free cleaning

Technical data:

- Liquid consumption: approx. 110 ml/min at 5 bar
- Viscosity range: 1 - 300 mm/sec. at 20° C
- Operating pressure: 2 - 8 bar
- Tank: 350 ml integrated, replaceable
- Air consumption: approx. 70 l/min at 6 bar
- Noise level: approx. 85 dB
- Pipe diameter: 7 mm
- Pipe length: 60 mm
- Pressure connector: 1/2 inch 7.2

Products for the electronic industry



- Pressure control integrated on the device
- Beam width: adjustable from approx. 1.5 mm to 3 mm
- Spray angle: approx. 15° - 20°

Numéro d'article	WL41058
Modèle	LicoJet Rubber
Fabricant	LICO-TEC
Numéro d'article du fabricant	200102
Données du fabricant du GPSR	Lico-Tec GmbH Lehmhäuserstr. 20 DE-94424 Arnstorf www.lico-tec.de
Unité de vente	1 pièce
Unité de contenu	1 pièce
Batterie incluse	non