

Chaussure de sécurité ESD, bleu 47



At ATLAS®, only the best quality cowhides are processed. Extremely careful selection ensures that only flawless, high-quality and soft leathers are used. The ATLAS SOFT nubuck leather has to withstand special challenges throughout the entire working day. The approx. 2mm thick full-grain cowhide leather is particularly characterised by its breathability and soft, comfortable feel.

ATLAS® brings together state-of-the-art technologies and the anatomical needs of every wearer. The new INNOFLEX SYSTEM® is a holistic running sole concept and supports the runner in every phase of movement. From the first to the last contact with the ground, the sole complex is permanently guided by the same, natural line of force, the INNOFLEX LINE. It optimally guides the forces from the heel to the toe and thus supports the natural line of force progression. Special areas such as the CLOUDZONE in the heel are responsible for the corresponding energy absorption, i.e. cushioning. The large-format tread surfaces, which are equipped with particularly energy-absorbing MPU® material, absorb the energy and return it to the movement process in a targeted manner. This

guarantees fatigue-free walking throughout the entire working day.

Alu-tec® technology: The new lightness. Aluminium has not only served as a high-tech material in aviation and the automotive industry for years, but also in many ATLAS safety shoes today. The anatomically shaped aluminium toe cap is particularly light and shifts the centre of gravity of the shoe to the middle of the foot. This actively helps to prevent tripping accidents caused by imbalance. The thermally neutral behaviour of aluminium also prevents cold bridges from forming inside the shoe and thus guarantees a pleasant foot climate in all seasons.

Especially when kneeling, wear and tear can occur in the area of the shoe toe after some time. These can be significantly reduced with the help of the abrasion-resistant MPU toe protector and the service life of the shoe is thus increased.

Particularly in everyday working life, with high physical stress, temperature-regulating properties are not only required, but expected. The aktiv-X functional lining stands for the highest quality, innovative technology and offers the wearer permanent, active moisture regulation. The aktiv-X functional lining regulates moisture and ensures that the shoes dry again quickly. It does not stain, is skin-friendly and abrasion-resistant.

Work healthier with the right cushioning. The new 3D cushioning system from ATLAS® enables noticeably gentle and fatigue-free walking. The basis for this outstanding walking comfort is formed by three basic components: Pressure relief. Cushioning. Dynamics. This is ensured by the perfect interaction of a pressure-relieving insole and the light and responsive MPU sole technology.

geeignet für die Einlagenversorgung-DGUV 112-191

ATLAS® offers you a wide range of different orthopaedic insoles. The articles marked here are suitable for orthopaedic insoles according to DGUV regulation 112-191. The marking on the shoe is decisive for this.

- EN ISO 20345 S1 SRC
- ESD (résistance de fuite <35 Megaohms)
- convient pour l'alimentation en inserts (DGUV 112-191/BGR 191)
- largeur standard W10, mais également disponible en W12 (ultra-large)

Numéro d'article	WL41683
Modèle	SL 80 blue 2.0 ESD
Gamme de modèles	SL 80 blue 2.0 ESD
Fabricant	ATLAS
Numéro d'article du fabricant	44700-47

Données du fabricant du GPSR	ATLAS-Schuhfabrik GmbH & Co.KG Frische Luft 159 DE-44319 Dortmund www.atlasschuhe.de
Longueur avec emballage	350 mm
Largeur avec emballage	250 mm
Hauteur avec emballage	150 mm
Unité de vente	1 paire
Unité de contenu	1 paire
Informations sur la couleur du fabricant	black / royal blue
Couleur	bleu, noir
Matériel	SOFT nubuck leather
Capuchon de protection	oui
Type de chaussures	chaussure de sécurité
Classe de sécurité	S2
Semelle de chaussure	MPU INNOFLEX system
Résistance au glissement	SRC
Largeur de la chaussure	W10 (largeur standard)
Caractéristiques (chaussures)	• Renfort aluminium alu-tec® • Système d'amortissement 3D • Réflecteurs de sécurité • rembourrage fonctionnel aktiv-X • Concept clima-stream® • Protection des pointes par fibres carbone • Technologie de semelles Light MPU®
Matériel (chaussures)	cuir nubuck
Pointure de chaussures UE	47
Conforme aux normes ESD	oui
Catégorie de risque (réglementation EPI)	Catégorie 2

Autres versions

Numéro d'article	Pointure de chaussures UE	Largeur de la chaussure
WL28435	36	W10 (largeur standard)
WL58611	36	W12
WL28436	37	W10 (largeur standard)
WL58612	37	W12

WL28437	38	W10 (largeur standard)
WL58613	38	W12
WL28438	39	W10 (largeur standard)
WL58614	39	W12
WL28439	40	W10 (largeur standard)
WL58615	40	W12
WL28440	41	W10 (largeur standard)
WL58616	41	W12
WL28441	42	W10 (largeur standard)
WL58617	42	W12
WL28442	43	W10 (largeur standard)
WL58618	43	W12
WL28443	44	W10 (largeur standard)
WL58619	44	W12
WL28444	45	W10 (largeur standard)
WL58620	45	W12
WL28445	46	W10 (largeur standard)
WL58621	46	W12
WL41683	47	W10 (largeur standard)
WL58622	47	W12
WL41684	48	W10 (largeur standard)
WL58623	48	W12
WL41685	49	W10 (largeur standard)
WL58624	49	W12