Station numérique à air chaud, fer à air chaud, 220-240 V.



The HCT2-200-21 Hot Air Pencil is a digital handheld convection tool that is ideally suited for light rework applications, which use smaller components and integrated circuits. As component miniaturization continues (i.e. 01005 components) the ergonomics of a pencil allow a user more freedom to access and rework components on the board without affecting adjacent parts. Larger handheld convection systems commonly reflow and dislodge adjacent components due to a higher minimum airflow. The HCT2 series of Digital Hot Air Pencils have always included an array of nozzle sizes and precision control. The HCT2-200's improved thermal performance allows the user to target a larger variety of components. Metcal has made working under a microscope easier with the optional bent nozzles. Add the HCT2-200-21 to your workbench and experience improved performance. HCT2-200-21 was developed for very small surface mount components and package sizes (1206s and smaller) and low board densities. For denser PCBAs or applications with heavy copper planes; boards > 4 layers; or components larger than 5mm, the use of a Metcal preheater (PCT-100 series) may be necessary.

• convient pour les applications de retouche légère
• pour les très petits composants montés en surface et les tailles de boîtier (1206 et moins)
• pour les circuits imprimés plus denses ou les applications comportant des zones de cuivre importantes
• Chauffage céramique de 200 watts et pompe à air à deux étages

• des régulateurs numériques de débit d'air et de température : deux écrans LED fournissent une représentation graphique et numérique du débit d'air et de la température souhaités
• Mode veille dès que la pièce à main est placée dans le plateau
• pièce à main ergonomique et légère
• y compris 6 buses (1,5 - 4 mm)

Numéro d'article	**WL44422**
Modèle	HCT-2-200-21
Fabricant	OKI
Numéro d'article du fabricant	HCT2-200-21
Données du fabricant du GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unité de vente	1 pièce
Unité de contenu	1 pièce
Fréquence	50/60 Hz
Puissance nominale	200 W
Tension	220 – 240 V
Plage de température °C	100 – 450 °C
Flux d'air	1,5 - 7 LPM
Température ambiante	10 – 40 °C
Conforme aux normes ESD	non