Tournevis ESD dynamométrique 1431, Micro ESD 5,0 - 11,0 Ncm



Torque tool with adjustable torque from 2.0 to 11.0 Ncm (precision ± 10%). Compact handle/interchangeable blade system for torque-controlled fine screw connections. The Kraftform Micro ESD torque screwdriver is ideal for torque-controlled screwdriving on electrostatically sensitive components. Suitable for holding bits with 4 mm half-moon drive (Wera series 9) and bits with 4 mm HIOS drive (Wera series 21). Tamper-proof. Clearly audible and perceptible disengagement when the set torque is reached. Unlimited manual release torque. Electrical surface resistance ≤ 10⁹ Ohm for reliable protection against electrostatic energy. Manufactured in accordance with DIN EN 61340-5-1. Handle/interchangeable blade system for lightning-fast blade replacement. Kraftform Micro handle with rotating cap and quick-twist zone for lightning-fast twirling, no more time-consuming regripping necessary. Power zone with integrated soft zones for transferring high loosening and tightening torques. Precision zone directly above the blade for the correct angle of rotation for adjustment work. Lightning-fast bit fixing: simply push the bit into the holder, automatic locking, secure fit. To change the bit, simply push the sleeve forwards and remove the bit. Free-running actuating sleeve for easy guidance of the tool during the screwdriving process. Bits suitable for manual and machine-operated screwdriving with electric screwdrivers (e.g. HIOS, Delvo, Sehan). Use e.g. on smartphones, cell phones, cameras, electronic devices, in dental laboratories and dental practices.

• Forme de force réglable Tournevis dynamométrique avec mandrin à changement rapide
• Un outil sûr sur le plan électrostatique grâce à une résistance de surface de < 10^9 Ohm
• Surcharge clairement audible et perceptible lorsque le couple de serrage est atteint
• Convient aux bits avec demi-lune de 4 mm et lecteur HIOS de 4 mm
• Utilisation par exemple sur les smartphones, les téléphones mobiles, les appareils photo et les dispositifs électroniques

Numéro d'article	**WL46880**
Modèle	1430 ESD Kraftform Micro
Fabricant	WERA
Numéro d'article du fabricant	05074804001

Données du fabricant du GPSR	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Longueur	145 mm
Largeur	23 mm
Hauteur	23 mm
Longueur avec emballage	145 mm
Largeur avec emballage	23 mm
Hauteur avec emballage	23 mm
Unité de vente	1 pièce
Unité de contenu	1 pièce
VDE	non
Conforme aux normes ESD	oui
Dimensions de l'emballage	unique
Type de tournevis	tournevis dynamométrique
Couple	0,05 – 0,11 Nm
Longueur de l'outil	145 mm