

## ESD pince coupante de côté - tête pointue et évidée

---



---

This is the narrowest head shape

The underside is relieved and facilitates optimum access even to extremely hard-to-reach areas

1 Million Movements - Magic Spring™ design enables maximum durability with constant spring force movements

Precision - Experience precise cuts from the high-precision screw joint that enables a smooth action with no jaw overlap

Uncompromising Swiss quality created to be strong, durable and sharp

Strong and Sharp - Hand-crafted cutting edges for superior strength and sharpness

Comfort, Security and Grip - Ergonomically-shaped handles provide superior comfort and fatigue-free handling with Maximum Opening Stop Technology

ESD Safe - made from ESD-safe material to prevent damage to sensitive components

Weller Erem® Cutters are designed to be strong, durable and sharp, having the highest precision available. Manufactured with uncompromising Swiss quality and created for worldwide applications, including electronics assembly and healthcare, Weller Erem

Cutters are built to last. The signature high-performance cutters set the industry standard with features that include Weller Erem Magic Spring™ providing over one million consistent, precise and accurate movements, High-Precision Screw Joint, and Maximum Opening Stop Technology. Feel the difference with Weller Erem® – the proven choice. Every time. 1500 Weller Erem pneumatic side cutters are light and precise. Thanks to a selection of different cutting heads they can operate extremely versatile. The cutters are suitable for cutting conventional components, soft metals or small plastic parts. The cutting heads can be interchanged easily.

- Il s'agit de la forme de tête la plus mince
- La partie inférieure est évidée et permet un accès optimal, même à des endroits extrêmement difficiles d'accès

|                                         |                                                                                        |
|-----------------------------------------|----------------------------------------------------------------------------------------|
| <b>Numéro d'article</b>                 | <b>WL51017</b>                                                                         |
| Fabricant                               | Weller Erem                                                                            |
| Numéro d'article du fabricant           | 592E                                                                                   |
| Données du fabricant du GPSR            | WELLER Tools GmbH<br>Carl-Benz-Strasse 2<br>DE-74354 Besigheim<br>www.weller-tools.com |
| Unité de vente                          | 1 pièce                                                                                |
| Unité de contenu                        | 1 pièce                                                                                |
| Batterie incluse                        | non                                                                                    |
| VDE                                     | non                                                                                    |
| Largeur de la tête                      | 11 mm                                                                                  |
| Conforme aux normes ESD                 | oui                                                                                    |
| Épaisseur de la tête                    | 6 mm                                                                                   |
| Longueur de la tête                     | 19 mm                                                                                  |
| Longueur de l'outil                     | 115 mm                                                                                 |
| Type de pinces coupantes latérales      | pinces coupantes de coté                                                               |
| Longueur de coupe                       | 12 mm                                                                                  |
| Valeur de coupe diamètre du fil (moyen) | 0,4 mm                                                                                 |
| Valeur de coupe diamètre du fil (doux)  | 0,8 mm                                                                                 |