

Treccia dissaldante ESD, gialla, larghezza 1,4 mm, lunghezza 1,5 m



For fast and efficient cleaning, the 1809-5F desoldering braid with a width of 1.4 mm, wetted with Rosin flux, is ideal for the production/repair of printed circuit boards in large quantities. The desoldering braid is a flux wetted copper braid that is used to remove solder so that components can be replaced and excess solder removed. The soldering iron is placed on the braid - as soon as both have been brought to the correct temperature, the flux is activated. The capillary action of the braid draws the solder up the wire. Techspray desoldering braids are available on ESD-safe spools and are therefore suitable for use with ESD-sensitive components.

- Fili di dissaldatura su rotolo ESD
- Trefolo impregnato con flusso di resina per un rapido assorbimento della saldatura

Articolo n.

WL15055

Products for the electronic industry



Modello	1809-5F
Produttore	TECHSPRAY
Codice articolo del produttore	1809-5F
Dati del produttore GPSR	TECHSPRAY ITW Saffierlaan 5 NL-2132 Hoofddorp www.techsprayeu.com
Lunghezza	1500 mm
Larghezza	1,4 mm
Unità di vendita	1 Rollo
Unità di contenuto	1 Rulli
Colore	Giallo
Incl. batteria	No
Standard	MIL-F-14256; NASA NHB 5300, 4 (34-1); NASA NPC 200-4; NASA SP5002; 1821: HP 8690-0588; 1823: HP 8690-0577; IPC Standard-J-STD-004
Conforme alla direttiva RoHS	Sì
Conforme alle ESD	Si

Altre versioni

Articolo n.	Larghezza	Lunghezza
WL15046	0,9 mm	3000 mm
WL15055	1,4 mm	1500 mm
WL15052	1,4 mm	3000 mm
WL15060	1,9 mm	1500 mm
WL15057	1,9 mm	3000 mm
WL15058	1,9 mm	30500 mm
WL15064	2,5 mm	1500 mm
WL15061	2,5 mm	3000 mm
WL15062	2,5 mm	30500 mm