Bit per viti con intaglio, 800/4 Z 0,5 x 3,0 x 70 mm



With the 800/4 Z screwdriver bit, slotted, 0.5 x 3.0 mm, 70 mm, Wera provides a precisely manufactured solution for slotted screw fastenings at a high quality level. The product is technically impressive for slotted screws. Even with sensitive components, the bit delivers consistently precise results - without compromise.

- per viti con intaglio
- Resistente e duro, per un uso universale
- 1/4" a trazione esagonale
- adatto per supporti secondo DIN ISO 1173-F 6.3

Articolo n.	**WL22853**
Modello	800/4 Z
Produttore	WERA
Codice articolo del produttore	05059466001
Dati del produttore GPSR	WERA Werkzeuge GmbH Korzerter Strasse 21-25 DE-42349 Wuppertal-Cronenberg www.wera.de
Lunghezza	70 mm
Larghezza	7 mm
Altezza	7 mm
Lunghezza con imballaggio	118 mm
Larghezza con imballaggio	35 mm
Altezza con imballaggio	15 mm
Contenuto della confezione	0,5x3,0x70
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Lunghezza del bit	70 mm
VDE	No
Tipo di vite	fessura
Conforme alle ESD	No

Lunghezza dell'utensile	70 mm
Diametro della lama	3 mm
Lunghezza della lama	70 mm
Lunghezza della lama in pollici	2,75 in
Larghezza della lama	3 mm
Spessore della lama	0,5 mm

Altre versioni

Articolo n.	Larghezza della lama	Spessore della lama	Lunghezza del bit
WL51597	3 mm	0,5 mm	50 mm
WL22853	**3 mm**	**0,5 mm**	**70 mm**
WL22854	3,5 mm	0,6 mm	70 mm
WL89760	3,5 mm	0,6 mm	152 mm
WL89752	4 mm	0,5 mm	50 mm
WL71953	4 mm	0,8 mm	50 mm
WL89764	4 mm	0,8 mm	70 mm
WL73439	4 mm	0,8 mm	89 mm
WL89761	4 mm	0,8 mm	152 mm
WL89753	4,5 mm	0,6 mm	50 mm
WL71800	4,5 mm	0,6 mm	89 mm
WL89754	5,5 mm	0,8 mm	50 mm
WL89755	5,5 mm	1 mm	50 mm
WL89765	5,5 mm	1 mm	70 mm
WL19121	5,5 mm	1 mm	89 mm
WL89762	5,5 mm	1 mm	152 mm
WL89756	6 mm	1 mm	50 mm
WL89757	6,5 mm	1,2 mm	50 mm
WL89766	6,5 mm	1,2 mm	70 mm
WL71801	6,5 mm	1,2 mm	89 mm
WL89763	6,5 mm	1,2 mm	152 mm
WL89758	8 mm	1,2 mm	50 mm
WL71802	8 mm	1,2 mm	89 mm
WL89759	8 mm	1,6 mm	50 mm

WL89767	8 mm	1,6 mm	89 mm