Punta di saldatura serie SxP, a forma di scalpello lungo 30° 2 x 16,04 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The SFP-series are nominally 390 ˚C. Metcal recommends the SFP-series for the majority of applications. However, the family also offer a higher temperature series designated SCP, nominally 450 ˚C, for high temperature and thermally demanding applications. STP-series are nominally 330 ˚C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

• per la maggior parte delle applicazioni standard

Articolo n.	**WL24727**

Modello	SFP-CHL20
Produttore	OKI
Codice articolo del produttore	SFP-CHL20
Dati del produttore GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Serie di prodotti	Serie SxP
Temperatura (max.)	421 °C
Serie di suggerimenti	SxP
Angolo (punta di saldatura)	30 °
Lunghezza della punta	16,04 mm
Larghezza della punta	2 mm
Forma della punta	scalpello
Allineamento della punta	Dritta
Temperatura della punta	421 °C
Manipolo corrispondente	MFR-H1-SC
Conforme alle ESD	No

Altre versioni

Articolo n.	Temperatura (max.)
WL27522	366 °C
WL24727	**421 °C**
WL27523	471 °C