Punta di saldatura serie SxP, angolata conica 0,4 x 15,21 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The SFP-series are nominally 390 ˚C. Metcal recommends the SFP-series for the majority of applications. However, the family also offer a higher temperature series designated SCP, nominally 450 ˚C, for high temperature and thermally demanding applications. STP-series are nominally 330 ˚C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

• per la maggior parte delle applicazioni standard

Articolo n.	**WL24730**
Modello	SFP-CNB04

Produttore	OKI
Codice articolo del produttore	SFP-CNB04
Dati del produttore GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Serie di prodotti	Serie SxP
Temperatura (max.)	421 °C
Serie di suggerimenti	SxP
Lunghezza della punta	15,21 mm
Larghezza della punta	0,4 mm
Diametro della punta di saldatura	0,4 mm
Forma della punta	angolato, conico
Allineamento della punta	Angolato
Temperatura della punta	421 °C
Manipolo corrispondente	MFR-H1-SC
Conforme alle ESD	No

Altre versioni

Articolo n.	Temperatura (max.)
WL26700	366 °C
WL24730	**421 °C**
WL26999	471 °C