Tunnel di rilavorazione della punta della serie RxP per SOIC-8



RxP-Blade/Quad Solder Tip Cartridges are the rework tips for the Metcal MFR-series soldering systems. The second letter in the part number designates the temperature series. RFP-Cartridges are nominally 390 ˚C. Metcal recommends the RFP temperature series for most applications. However, there is a higher temperature range designated RCP, nominally 450 ˚C, for high temperature and thermally demanding applications. Can be used with leaded and lead-free solder. The Metcal SmartHeat®-Technology“ will adjust the power levels during soldering to suit the application.

- per la maggior parte delle applicazioni standard
- adatto per le serie MFR-1100 e MFR-2200

Articolo n.	**WL24743**
Modello	RFP-DL2
Produttore	OKI

Codice articolo del produttore	RFP-DL2
Dati del produttore GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Serie di prodotti	Serie RxP
Tipo di punta	Tunnel-Rework Lötpatonen
Serie di suggerimenti	RxP
Progettazione SMT	SOIC-8
Dimensioni della punta	5,18 x 4,23 mm
Larghezza della punta	2,29 mm
Forma della punta	trafori
Allineamento della punta	Dritta
Manipolo corrispondente	MFR-H1-SC
Conforme alle ESD	No

Altre versioni

Articolo n.	Progettazione SMT
WL24743	**SOIC-8**
WL24742	SOIC-14-16
WL27216	SOIC-16