Punta di dissaldatura serie DxP, D: 2,44 / 3,65 mm



DxP-Desolder Tips are the standard desoldering tip range for the Metcal desolder series MFR-1150, MFR-1350, MFR-1351 and MFR-UK5. The second letter in the part number designates the temperature series. The temperature series DFP are nominally 390 ˚C. Metcal recommends the DFP-series for most applications. The Temperature series DCP are nominally 450 ˚C and are recommended for high temperature and thermally demanding applications. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- per la maggior parte delle applicazioni standard
- adatto per i sistemi di dissaldatura MFR-1150, MFR-1350, MFR-1351

Articolo n.	**WL24760**
Modello	DFP-CN7
Produttore	OKI

Codice articolo del produttore	DFP-CN7
Dati del produttore GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Serie di prodotti	Serie DxP
Temperatura (max.)	421 °C
Serie di suggerimenti	DxP
Diametro interno	2,44 mm
Diametro esterno	3,65 mm
Lunghezza della punta	5,54 mm
Forma della punta	conico
Allineamento della punta	Dritta
Temperatura della punta	421 °C
Manipolo corrispondente	MFR-HDS
Conforme alle ESD	No

Altre versioni

Articolo n.	Diametro interno
WL24755	0,64 mm
WL24756	0,79 mm
WL24757	1,05 mm
WL24758	1,31 mm
WL24759	1,55 mm
WL24760	**2,44 mm**