Punta di saldatura a scalpello a 30° 2,5 x 10 mm della serie SxP



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The Temperature series SFP are nominally 390 ˚C. Metcal recommends the SFP-series for the majority of applications. However, the family also offer a higher temperature serie designated SCP, nominally 450 ˚C, for high temperature and thermally demanding applications. STP-series are nominally 330 ˚C for light load applicationCan be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

• adatto per la ceramica e per applicazioni con elevati requisiti termici

Articolo n.	**WL26997**

Modello	SCP-CH25
Produttore	OKI
Codice articolo del produttore	SCP-CH25
Dati del produttore GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Serie di prodotti	Serie SxP
Temperatura (max.)	471 °C
Serie di suggerimenti	SxP
Angolo (punta di saldatura)	30 °
Lunghezza della punta	10 mm
Larghezza della punta	2,5 mm
Forma della punta	scalpello
Allineamento della punta	Angolato
Temperatura della punta	460 °C
Manipolo corrispondente	MFR-H1-SC
Conforme alle ESD	No

Altre versioni

Articolo n.	Temperatura (max.)
WL25884	366 °C
WL24724	421 °C
WL26997	**471 °C**