Punta di dissaldatura serie DxP, D: 0,64 /1,8 mm



DxP-Desolder Tips are the standard desoldering tip range for the Metcal desolder series MFR-1150, MFR-1350, MFR-1351 and MFR-UK5. The second letter in the part number designates the temperature series. The temperature series DFP are nominally 390 ˚C. Metcal recommends the DFP-series for most applications. The Temperature series DCP are nominally 450 ˚C and are recommended for high temperature and thermally demanding applications. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- adatto per la ceramica e per applicazioni con elevati requisiti termici
- adatto per i sistemi di dissaldatura MFR-1150, MFR-1350, MFR-1351

Articolo n.	**WL27284**
Modello	DCP-CN2

Produttore	OKI
Codice articolo del produttore	DCP-CN2
Dati del produttore GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Serie di prodotti	Serie DxP
Temperatura (max.)	471 °C
Serie di suggerimenti	DxP
Diametro interno	0,64 mm
Diametro esterno	1,8 mm
Lunghezza della punta	5,54 mm
Forma della punta	conico
Allineamento della punta	Dritta
Temperatura della punta	460 °C
Manipolo corrispondente	MFR-HDS
Conforme alle ESD	No

Altre versioni

Articolo n.	Diametro interno
WL27284	**0,64 mm**
WL25296	0,79 mm
WL25295	1,05 mm
WL27568	1,31 mm
WL25297	1,55 mm
WL25298	2,44 mm