

## Punta di saldatura serie SxP a forma di scalpello 30° 3 x 11 mm



SxP-Solder Tip Cartridges are the standard soldering tip range for the Metcal MFR-1110, MFR-2210 and MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The SFP temperature series are nominally 390 °C. Metcal recommends the SFP-series for most applications. However, Metcal offers a higher temperature series designated SCP, nominally 450 °C, for high temperature and thermally demanding applications. STP-series are nominally 330 °C for light load application. Can be used with leaded and lead-free solder. The Metcal "SmartHeat®-Technology" adjusts power levels automatically based on the demand of the application.

- per applicazioni sensibili alla temperatura

Articolo n.	WL27525
Modello	STP-CH30
Produttore	OKI

Products for the electronic industry



Codice articolo del produttore	STP-CH30
Dati del produttore GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Serie di prodotti	Serie SxP
Temperatura (max.)	366 °C
Serie di suggerimenti	SxP
Angolo (punta di saldatura)	30 °
Lunghezza della punta	11 mm
Larghezza della punta	3 mm
Forma della punta	scalpello
Allineamento della punta	Angolato
Temperatura della punta	365 °C
Manipolo corrispondente	MFR-H1-SC
Conforme alle ESD	No

## Altre versioni

Articolo n.	Temperatura (max.)
<b>WL27525</b>	<b>366 °C</b>
WL26974	421 °C
WL27526	471 °C