Punta di saldatura serie SxV a scalpello 5 x 11,3 mm



SxV-Solder Tips are the standard soldering tip range for the Metcal PS-900/MFR1100, MFR-2210, MFR-1351-series soldering systems. The second letter in the part number designates the temperature series. The temperature series SFV are nominally 390 ˚C. Metcal recommends the SFV-series for the majority of applications. However, the family also offer a higher temperature serie designated SCV, nominally 450 ˚C, for high temperature and thermally demanding applications. STV-series are nominally 330 ˚C for light load application. Can be used with leaded and lead-free solder The Metcal "SmartHeat®-Technology" automatically adjusts power levels during each soldering operation.

- adatto per la ceramica e per applicazioni con elevati requisiti termici
- ottimizzato per le prestazioni termiche
- adatto per i manipoli dei sistemi PS e MFR

Articolo n.	**WL27891**

Modello	SCV-CH50A
Produttore	OKI
Codice articolo del produttore	SCV-CH50A
Dati del produttore GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.ok-international.com
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Serie di prodotti	Serie SxV
Temperatura (max.)	471 °C
Serie di suggerimenti	SxV
Lunghezza della punta	11,3 mm
Larghezza della punta	5 mm
Forma della punta	scalpello
Allineamento della punta	Dritta
Temperatura della punta	460 °C
Conforme alle ESD	No

Altre versioni

Articolo n.	Temperatura (max.)
WL27890	366 °C
WL27889	421 °C
WL27891	**471 °C**