Treccia dissaldante ESD NO CLEAN, verde, larghezza 1,9 mm, lunghezza 30,5 m



Techspray 1822-100F No-Clean desoldering braid with a width of 1.9 mm leaves no ionic flux residues that can accumulate and form branches, so-called "dendrites". The desoldering braid is a copper braid wetted with flux that is used to remove solder so that components can be replaced and excess solder removed. The soldering iron is placed on the braid - as soon as both have been brought to the correct temperature, the flux is activated. The capillary action of the braid draws the solder up the wire. Techspray desoldering braids are available on ESD-safe spools and are therefore suitable for use with ESD-sensitive components.

- Fili di dissaldatura NO CLEAN su rotolo ESD
- Assorbimento particolarmente veloce dello stagno
- Residui senza alogeni, non conduttivi
- Impregnato con disossidante appositamente sviluppato per evitare residui di disossidante ionico

Articolo n.	**WL27946**
Modello	1822-100F
Produttore	TECHSPRAY
Codice articolo del produttore	1822-100F
Dati del produttore GPSR	TECHSPRAY ITW Saffierlaan 5 NL-2132 Hoofddorp www.techsprayeu.com
Lunghezza	30500 mm
Larghezza	1,9 mm
Unità di vendita	1 Rollo
Unità di contenuto	1 Rulli
Colore	Verde Ecologica
Standard	MIL-F-14256; NASA NHB 5300, 4 (34-1); NASA NPC 200-4; NASA SP5002; 1821:HP 8690-0588; 1823: HP 8690-0577; IPC Standard-J-STD-004
Conforme alla direttiva RoHS	Sì
Conforme alle ESD	Si

Altre versioni

Articolo n.	Larghezza	Lunghezza
WL15070	0,9 mm	3000 mm
WL15073	1,4 mm	1500 mm
WL15072	1,4 mm	3000 mm
WL15075	1,9 mm	1500 mm
WL15074	1,9 mm	3000 mm
WL27946	**1,9 mm**	**30500 mm**
WL15077	2,5 mm	1500 mm
WL15076	2,5 mm	3000 mm
WL26404	2,5 mm	30500 mm
WL15079	3,3 mm	1500 mm