Stazione di saldatura a due canali 230 Volt, con manipolo MX-H1-AV e MX-DS1



The MX-5200 Soldering, Desoldering, and Rework Series has increased power and process control, with dual-simultaneous ports for two users or a single user with dual applications. The MX-5200 can be operated with two handpieces dynamically sharing the 80-watt output power based on demand, adding even more application flexibility and speed. A built-in Net Power Meter displays a graphical and numerical representation of the power applied to the cartridge. User Programmable Power Save Mode: the time to enter Power Save Mode is adjustable from 10 to 120 minutes. Ground Fault Interrupt: AC ground monitor detects power line ground failures and immediately alerts the operator and shuts down the system. Universal Power Supply: automatically senses the input line voltage and adjusts accordingly, which allows for worldwide operation without adaptors or a change in performance. Full compatibility with existing and previous MX upgrade kits, tip-cartridges, handpieces, and accessories.

FAST TIME-TO-RECOVERY:
Delivers increased production rates and throughput no matter the application. The MX-5200 super-charged power supply seamlessly tackles the challenges of high-mass components, multilayered boards, and lead-free solders.

SMARTHEAT® PROCESS CONTROL:
The technology built into every Metcal SmartHeat® system means that soldering and rework are always performed at safe, controlled temperatures. Metcal users know that moderate fixed temperatures, where power is varied, provide the best assurance for a well-controlled soldering and rework process.
• 80 watt
• 230 volt

Articolo n.	**WL27989**
Modello	MX-5251
Produttore	METCAL
Codice articolo del produttore	MX-5251
Dati del produttore GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.metcal.com
Contenuto della confezione	Unità di alimentazione (MX-PS5200) Manipolo (MX-H1-AV e MX-DS1) Stoccaggio (MX-W1AV e MX-W5DS)
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Energia	125 W
Voltaggio	240 V
Stazione (tipo)	Stazione Di Dissaldatura, Stazione Di Saldatura
Temperatura ambiente	10 – 40 °C
Conforme alle ESD	No