

Stazione di saldatura a due canali 230 Volt saldatore MX-H1-AV



The MX-5200 Soldering, Desoldering, and Rework Series has increased power and process control, with dual-simultaneous ports for two users or a single user with dual applications. The MX-5200 can be operated with two handpieces dynamically sharing the 80-watt output power based on demand, adding even more application flexibility and speed. A built-in Net Power Meter displays a graphical and numerical representation of the power applied to the cartridge. User Programmable Power Save Mode: the time to enter Power Save Mode is adjustable from 10 to 120 minutes. Ground Fault Interrupt: AC ground monitor detects power line ground failures and immediately alerts the operator and shuts down the system. Universal Power Supply: automatically senses the input line voltage and adjusts accordingly, which allows for worldwide operation without adaptors or a change in performance. Full compatibility with existing and previous MX upgrade kits, tip-cartridges, handpieces, and accessories.

FAST TIME-TO-RECOVERY:

Delivers increased production rates and throughput no matter the application. The MX-5200 super-charged power supply seamlessly tackles the challenges of high-mass components, multilayered boards, and lead-free solders.

SMARTHEAT® PROCESS CONTROL:

The technology built into every Metcal SmartHeat® system means that soldering and rework are always performed at safe, controlled temperatures. Metcal users know that moderate fixed temperatures, where power is varied, provide the best assurance for a well-controlled soldering and rework process.

- 80 watt
- 2 canali
- Tipo di display LCD
- ESD solo

N. articolo	WL28208
Modello	MX-5210
Produttore	METCAL
Produttore Articolo n.	MX-5210
Informazioni sul produttore del GPSR	OK International Ltd Eagle Close, Chandlers Ford GB-SO53 4NF Hampshire www.metcal.com
Dotazione di fornitura	Unità di alimentazione MX-PS5200 Saldatore MX-H1-AV Scaffale MX-W1AV (con abbassamento della temperatura)
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
potere	125 W
Tensione	240 V
tipo di stazione	Stazione Di Dissaldatura, Stazione Di Saldatura
Conforme alle norme ESD	No