# Fili di dissaldatura




Ersa desoldering braids are provided with halogen-free no-clean flux and are ideal for gently removing excess or old solder, especially from SMD-equipped PCBs. The fine copper mesh with high capillary force and a width of 1.5 mm guarantees the best desoldering results. In some cases, the additional use of a flux cream can be helpful.
• ERSA Dissaldatura senza pulizia
• I fili di dissaldatura ERSA No-Clean sono adatti per una rimozione efficace e delicata di vecchie saldature, specialmente su circuiti stampati SMD
• La maglia fine e l'elevata capillarità e il contenuto di flusso ottimale garantiscono i migliori risultati di dissaldatura.

| | |
|---|---|
| **Articolo n.** | **WL36490** |
| Modello | 0WICKNC1.5/10 |
| Produttore | ERSA |

| | |
|---|---|
| Codice articolo del produttore | 0WICKNC1.5 |
| Dati del produttore GPSR | ERSA GmbH<br>Leonhard-Karl-Strasse 24<br>DE-97877 Wertheim<br>www.ersa.de |
| Lunghezza | 1500 mm |
| Larghezza | 1,5 mm |
| Lunghezza con imballaggio | 112 mm |
| Larghezza con imballaggio | 55 mm |
| Altezza con imballaggio | 55 mm |
| Unità di vendita | 1 Rollo |
| Unità di contenuto | 1 Rulli |
| Colore | Giallo |
| Conforme alla direttiva RoHS | Sì |
| Conforme alle ESD | No |

## Altre versioni

| Articolo n. | Larghezza |
|---|---|
| **WL36490** | **1,5 mm** |
| WL36491 | 2,7 mm |
| WL36492 | 4,9 mm |