

Unità di aspirazione fumi di saldatura, 2 ugelli di aspirazione 80 m³/h a 1900 Pa



The WSA-10LR extraction unit for solder fumes has 2 extraction ports with an outer diameter of 50 mm (top), 4 adjustable blow-out gills (both sides, bottom), an optical filter indicator and a volume flow controller.

How does the WSA-10LR extraction unit work: An EC blower with a high pressure reserve generates a volumetric flow suitable for the application on the clean gas side of the filter. The volumetric flow can be controlled individually and steplessly. In this way, the pollutant-laden raw gas is extracted in a reliable manner. When soldering work is performed, soldering smoke forms out of vaporizing flux, small quantities of solder and gas-emitting substances from working circuit boards and components. This is comprised of a mixture of adhesive aerosols, particles and gases that must be removed from the raw gas.

The filter set-up used is specially designed for this purpose. An upstream filter mat

combination retains cooled, sticky aerosols in the suction line and prevents premature clogging of the subsequent H13 main filter element. Regularly changing the filter mat combination M5/F7 at shorter intervals significantly extends the functionality of the main filter. The particles contained in the soldering smoke are precipitated in a multi-stage storage filter system. Thanks to their depth penetration, the filter mats used are particularly suitable for the precipitation of soldering smokes. A majority of the particles contained in the soldering smoke are trapped at this stage. Extremely fine suspended substances are held back by the High Efficiency Particulate Air filter H13 in the combined filter cassette H13A. This guarantees a particle precipitation rate of 99.95%. The precipitation (adsorption) of gaseous and vaporous air contaminations takes place in the activated carbon bed of the combined filter cassette H13A. The filter effect of the activated carbon is based on adsorption, i.e. on the depositing of (gaseous) substances on the surface of the activated carbon.

In general, no chemical changes of the adsorbed substance take place in physical adsorption. The nominal volumetric flow of the devices is based on the filter construction, the contact period is oriented to a medium adsorption response. Thanks to the high degree of cleaning, the filtered clean gas can then be returned to the working area (recirculated-air operation). This avoids any loss of heat. Recirculated air operation is not permitted for the suctioning and filtration of carcinogenic, mutagenic or reprotoxic substances.

- Apparecchi per l'estrazione e la filtrazione di fumi, gas e vapori di saldatura in miscele di aria non esplosiva
- 2 attacco di aspirazione DN50
- per 1-2 postazioni di lavoro
- Uscita aria: lame, entrambi i lati, regolabili
- Colore RAL 7035
- Equipaggiamento: soffiatore, azionamento EC esente da manutenzione, controllo del flusso volumetrico, visualizzazione dell'occupazione del filtro antiparticolato
- Filtro costituito da: filtro in lamiera stirata (opzionale), tappetino filtrante M5/F7, cassetta filtro combinato H13A

Articolo n.	WL37327
Modello	WSA-10LR
Produttore	WEIDINGER
Codice articolo del produttore	2-00020
Dati del produttore GPSR	Weidinger GmbH Hertha-Sponer-Str. 1a DE-82216 Gernlinden www.weidinger.eu
Lunghezza	400 mm

Larghezza	350 mm
Altezza	500 mm
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Potenza nominale (motore)	0,15 kW
Portata nominale	80 m ³ /h a 1900 Pa
Frequenza	50/60 Hz
Corrente nominale	0,95 A
Voltaggio	230 V
Vuoto (max.)	3200 Pa
Livello sonoro	45 – 49 dBA
Portata volumetrica (max.)	190 m ³ /h