

WXUP MS, saldatore ultra, 150 W, tecnologia Active-Tip



Production within the electronics, medical technology and aerospace industries is moving faster as components become smaller, more sensitive, complex and more powerful. The soldering industry is not different. With the Weller RT MS tips you meet these increasing demands and provide maximum protection to the printed circuit board and the component you're soldering. With the MS tips you achieve the best results and keep your operation costs as low as possible. The Weller MS (military standard) soldering tips with active tip technology are fully compliant with IPC industry standards (IPC - TM-650 2.5.33 Measurement of Electrical Overstress from Soldering Hand Tools) and are also MIL-SPEC compliant. Extend your Weller WX workbench with a micro soldering tool.

- Saldatore Intelligent Ultra 150 W, 24 V
- Standard militare (MIL-SPEC)
- Per componenti di grandi dimensioni con elevato fabbisogno energetico
- Saldatore per stazioni di saldatura WX
- Memoria dei parametri nel pistone, ad es. temperature di standby, tempo di spegnimento automatico
- Riduzione dei costi di consumo (radiatori e punte di saldatura) grazie al sensore di utilizzo
- Cambio veloce e senza attrezzi delle punte di saldatura RTU
- Il sistema attivo della punta di saldatura (cartuccia) permette di cambiare l'intera punta di saldatura quando il saldatore è caldo

- senza punte di saldatura
- Tempo di riscaldamento (circa) in secondi (50-350°C / 120-660°F): 7 sec.
- Tecnologia del radiatore Active Tip

Articolo n.	WL46740
Modello	WXUP MS
Specifica	MIL-SPEC
Tecnologia	Active-Tip
Produttore	WELLER
Codice articolo del produttore	T0052923099
Dati del produttore GPSR	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller-tools.com
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Incl. batteria	No
Energia	150 W
Voltaggio	24 V
Manipolo (tipo)	Saldatrici
Supporto coordinato	WSR 200
Suggerimenti per l'abbinamento	RTU MS
Serie di suggerimenti	RTU-MS
Unità di controllo corrispondente	WX 1, WX 2, WXD 2, WXA 2, WXR 3
Conforme alle ESD	Si