

## ESD Tronchese con testa a taglio laterale – testa ovale

---



---

Side cutter 622N + "W" = wire holder

W : Safety device for holding wire scraps This safety device for side cutters holds wire scraps securely after cutting. Available for all Series 500, 600, 2400 & 2600 cutters. Order suffix "W", e.g.595EW

W : Safety device for holding wire scraps This safety device for side cutters holds wire scraps securely after cutting. Available for all Series 500, 600, 2400 & 2600 cutters. Order suffix "W", e.g.595EW

This is the most widely used head shape.

Fits for all cutting applications where easy access is given

It is robust and size for size offers the highest cutting capacity.

Side cutter 622N + "W" = wire holder

1 Million Movements - Magic Spring™ design enables maximum durability with constant spring force movements

Precision - Experience precise cuts from the high-precision screw joint that enables a smooth action with no jaw overlap

---

Products for the electronic industry



Uncompromising Swiss quality created to be strong, durable and sharp

Strong and Sharp - Hand-crafted cutting edges for superior strength and sharpness

Comfort, Security and Grip - Ergonomically-shaped handles provide superior comfort and fatigue-free handling with Maximum Opening Stop Technology

ESD Safe - made from ESD-safe material to prevent damage to sensitive components

Weller Erem® Cutters are designed to be strong, durable and sharp, having the highest precision available. Manufactured with uncompromising Swiss quality and created for worldwide applications, including electronics assembly and healthcare, Weller Erem Cutters are built to last. The signature high-performance cutters set the industry standard with features that include Weller Erem Magic Spring™ providing over one million consistent, precise and accurate movements, High-Precision Screw Joint, and Maximum Opening Stop Technology. Feel the difference with Weller Erem® – the proven choice. Every time. 1500 Weller Erem pneumatic side cutters are light and precise. Thanks to a selection of different cutting heads they can operate extremely versatile. The cutters are suitable for cutting conventional components, soft metals or small plastic parts. The cutting heads can be interchanged easily.

- Si tratta della forma di testa più utilizzata.
- Adatta a tutte le applicazioni di taglio, dove è presente un facile accesso
- È robusta, e offre la massima capacità di taglio.
- Tronchese con taglio laterale, testa ovale, uguali al modello 622N (T622N), con dispositivo opzionale di sicurezza "raccogli fili"

|                                |                                                                                        |
|--------------------------------|----------------------------------------------------------------------------------------|
| <b>Articolo n.</b>             | <b>WL50985</b>                                                                         |
| Produttore                     | Weller Erem                                                                            |
| Codice articolo del produttore | 622NW                                                                                  |
| Dati del produttore GPSR       | WELLER Tools GmbH<br>Carl-Benz-Strasse 2<br>DE-74354 Besigheim<br>www.weller-tools.com |
| Unità di vendita               | 1 Pezzo                                                                                |
| Unità di contenuto             | 1 Pezzo                                                                                |
| Incl. batteria                 | No                                                                                     |
| VDE                            | No                                                                                     |
| Larghezza della testa          | 9 mm                                                                                   |
| Conforme alle ESD              | Si                                                                                     |
| Spessore della testa           | 6 mm                                                                                   |
| Lunghezza della testa          | 17 mm                                                                                  |
| Lunghezza dell'utensile        | 110 mm                                                                                 |
| Tipo di tronchesi laterali     | Taglierina Laterale                                                                    |

|                                                |        |
|------------------------------------------------|--------|
| Lunghezza di taglio                            | 10 mm  |
| Diametro del filo del valore di taglio (medio) | 0,8 mm |
| Diametro del filo di taglio (morbido)          | 1,3 mm |