

Saldatore PYROPEN PIEZO, Profi-Line, a gas butano (autoaccensione, senza gas)



The Weller Pyropen Piezo Butane gas soldering iron is a self igniting soldering iron with solder and hot blow functions. The tool has a rapid heat up time and one filling of Butane gas lasts up to 3 hours. It's ideal for soldering on the go and helps to complete soldering tasks anywhere, without the need for a mains supply or an obstructing cable. It is temperature adjustable between 250°C to 500°C when used as a soldering iron and up to 650°C when used as a hot air blower. Due to its piezo igniter the Weller Pyropen can be conveniently turned on without the need of another tool.

Solder on the go, even outdoors - Complete your soldering task anywhere, without the need for a mains supply or an obstructing cable in the way. Set in metal box. Self-Igniting Piezo function - Convenient one hand start with self-igniting push button piezo ignition, without the need of another tool. Temperature adjustable from 250° to 650°C - variable adjustable temperatures can be set between 250° and 500°C when used as soldering

iron, and 650°C when used as hot air blower. Easy refill with Weller butane gas - No need for cords, batteries or cartridges, easy refill with Weller butane gas in just a few seconds for an almost uninterrupted workflow. High versatility with included accessories - with additional hot air blower function for shrinking hoses. Ready to use within seconds - Rapid heat up time, no long waiting for heating up the iron. Extra long operation time – butane gas soldering iron works approximately 3 hours with one filling of Weller Butane gas.

- with piezo ignition
- filling quantity: 28 ml - sufficient for approx. 2 hours
- Comparison to electrical power: 20 - 80 W

N. articolo	WL63529
Modello	Pyropen Piezo
Produttore	WELLER
Produttore Articolo n.	T0051605899
Informazioni sul produttore del GPSR	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
Unità di vendita	1 Pezzo
Unità di contenuto	1 Pezzo
Manipolo Tipo	Saldatore A Gas
Suggerimenti	Serie 70-x
controllore appropriato	Gas betrieben
Conforme alle norme ESD	No