

## PT P7 Punta Tonda Lunga 425°C Larghezza, 0,8 mm

The Weller Magnastat system operates through a ferro-magnetic sensing device which changes its characteristics when specific temperatures are reached. This causes it to either attract or repel a permanent magnet which operates a power supply switch. In this way power to the heating element can be quickly switched on or off to either provide extra power for soldering operations or reduce power when idling. Various pre-selected tip temperatures are available to permit different types of soldering to be undertaken. Working temperature selection is achieved by simply changing the temperature sensing; soldering tip. These are available in temperature ratings of 260°C, 310°C, 370°C, 425°C and 480°C.

|                                      |                                                                                 |
|--------------------------------------|---------------------------------------------------------------------------------|
| <b>N. articolo</b>                   | <b>WL63594</b>                                                                  |
| Modello                              | PT P7                                                                           |
| Produttore                           | WELLER                                                                          |
| Produttore Articolo n.               | 4PTP7-1                                                                         |
| Informazioni sul produttore del GPSR | WELLER Tools GmbH<br>Carl-Benz-Strasse 2<br>DE-74354 Besigheim<br>www.weller.eu |
| Unità di vendita                     | 1 Pezzo                                                                         |
| Unità di contenuto                   | 1 Pezzo                                                                         |
| diametro                             | 6,9 mm                                                                          |
| Serie di punte di saldatura          | PT                                                                              |
| lunghezza del picco                  | 44 mm                                                                           |
| larghezza del picco                  | 0,3 mm                                                                          |
| forma di picco                       | rotonda                                                                         |
| allineamento dei picchi              | Dritta                                                                          |
| Manipolo adatto                      | FE 50M, TCP 12, TCP 24, TCP 42, TCPS                                            |
| manipolo abbinato                    | tcp24, tcps, tcp12, tcp42, fe50m                                                |
| Conforme alle norme ESD              | No                                                                              |