

## Soldeerdraad Sn96,5Ag3Cu0,5/FG 3,5%, 1,5 mm, 1 kg



- Flux type C3+ (loodvrij)
- Legering Sn96,5Ag3Cu0,5/FG 3,5 %/1-streng
- Classificatie ROL0 1.1.3, F-SW32
- Microlegering MA-S
- voor hoge weerstand tegen oxidatie
- D = 1,5 mm, 1 rol = 1 kg

[<https://www.tamura-elsold.de/index.php/en/downloads/safety-data-sheets-sds>Please download here the suitable safety data sheet]

Artikelnr.	WL30861
Model	Flussmitteltyp C3+ (bleifrei)
Fabrikant	TAMURA ELSOLD
Fabrikant artikelnr.	RÖLOT8045

Products for the electronic industry



GPSR-fabrikantgegevens

TAMURA DEUTSCHLAND GmbH  
Hüttenstraße 1  
DE-38871 Ilsenburg  
www.tamura-elsold.de

Verkoopeenheid	1 rollen
Inhoudseenheid	1 Rollen
Diameter	1,5 mm
Fluxklasse	1.1.3, ROLO
Legering	Sn96,5Ag3Cu0,5
Vloeistoftype	C3+
Fluxinhoud	3,5 %
Loodvrij/loodhoudend	ongelood

