

WR 2, cyfrowy 2-kanalowy zasilacz, 250 W (300 W)



Rework on highest level

One station meets the requirements of a rework workplace. Unique connecting compatibility of all tools. 2 independent tool channels with automatic tool recognition guarantee the simultaneous operation of 2 soldering tools. Tools are permanently ready for use.

The Weller Rework station WR 2 is a versatile soldering and desoldering station for professional repair work on electronic components of the latest technology in industrial production technology as well as in the repair and laboratory sector. The WR 2 has two independent tool-specific channels with automatic tool recognition and activation. Simultaneous soldering and desoldering or soldering and hot air soldering is thus possible at any time. With the exception of the Weller High-Speed Tools, all soldering tools such as soldering irons, solder baths, desoldering irons or hot air irons can be operated with the rework station.

- 2 niezależne kanały narzędziowe z automatycznym rozpoznaniem narzędzia

Products for the electronic industry



- Praca maksymalnie 2 narzędzi jednocześnie
- Wyłącznik nadprądowy: 1,6 A
- Zgodność z IPC: Grot lutowniczy (Tip to ground) odpowiada IPC-J-001
- Wbudowana pompa: Praca przerywana 30/30 s
- Wyświetlacz: LCD
- Połączenie wyrównawcze
- Kompatybilność z WT
- Interfejs USB

Numer artykułu.	WL26390
Model	WR 2
Linia modelowa	WR 2
Producent	WELLER
Numer artykułu producenta.	T0053377699N
Dane producenta GPSR	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller.eu
Długość	280 mm
Szerokość	240 mm
Wysokość	103 mm
Zakres dostawy	Control unit WR 2
Długość w calach	11,02 in
Szerokość w calach	9,45 in
Wysokość w calach	4,06 in
Jednostka sprzedaży	1 sztuka
Jednostka treści	1 sztuka
Moc	300 W
Woltaż	230 V
Objętość powietrza (maks.)	10 l/min
Zakres temperatur °C	50 – 550 °C
Zakres temperatur °F	150 – 999 °F
Dokładność temperatury °F	±17 °F
Stabilność temperatury °C	±2 °C
Stabilność temperatury °F	±4 °F
Próżnia	0,7 Bar
Liczba kanałów	2