WXD 2, 2-kanałowa jednostka zasilająca, 200 W (255 W)



Remove solder with the fastest desoldering irons in the world

External compressed air supply
The maintenance-free Venturi unit produces a constant vacuum using an external compressed air supply.

Fastest desoldering iron
With its 120 watts and extremely short heating time, the desoldering iron can easily handle jobs that would have been difficult in the past, including desoldering high mass PCBs.

No tedious cleaning
The new, extended nozzle shaft prevents the suction tube from sticking. Since the suction channel has also been replaced, the once tedious and time-consuming task of leaning the tool is now a thing of the past.

Quick replacement
Thanks to ingenious mountings, the suction nozzle and solder cartridge can be changed quickly and easily – without the risk of burns or tricky replacement work.

Huge cost savings
The relatively low operating temperature (380°C) and automatic standby mode controlled by the use sensor increase the service life of the suction nozzles by a factor of 3.

Vacuum run-on
A vacuum run-on time can be set to prevent the suction pump blocking.

Two models are available.
The WXDP 120 is designed for horizontal operation and the WXDV 120 for vertical operation.
• do pracy z zewnętrznym zasilaniem w sprężone powietrze
• mniej przeróbek dzięki optymalnemu wykorzystaniu narzędzi i odpowiedniej temperaturze pracy
• Niższe koszty eksploatacji dzięki wydłużonej żywotności dysz rozlutowniczych
• Narzędzie rozlutownicze z opcją stanu czuwania
• Wyświetlacz: 255 x 128 punktów / podświetlenie tła
• Przyłącze sprężonego powietrza: Średnica zewnętrzna 6 mm (0,24"), suche sprężone powietrze bez zawartości oleju
• Kompatybilność z WX
• Połączenie wyrównawcze
• Zgodność z IPC
• Podciśnienie: maks. 55 kPa (8psi)
• Interfejs USB

Numer artykułu.	**WL27062**
Model	WXD 2
Linia modelowa	WXD 2
Producent	WELLER
Numer artykułu producenta.	T0053426399N
Dane producenta GPSR	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller-tools.com
Długość	174 mm
Szerokość	154 mm
Wysokość	135 mm

Długość w calach	6,69 in
Szerokość w calach	5,94 in
Wysokość w calach	5,12 in
Jednostka sprzedaży	1 sztuka
Jednostka treści	1 sztuka
Moc	255 W
Bezpiecznik	T2A
Woltaż	230 V
Zakres temperatur °C	50 – 550 °C
Zakres temperatur °F	150 – 999 °F
Dokładność temperatury °F	±17 °F
Zużycie powietrza	35 l/min
Stabilność temperatury °C	±2 °C
Stabilność temperatury °F	±4 °F
Liczba kanałów	2