

1-kanalowa jednostka zasilająca, 150 W



This is how soldering is done today

When 90 watts are not enough, the high-power version with 150 watts is the right solution. The new powerful WT soldering stations set new standards in terms of user-friendliness. The detailed LC display provides a detailed overview of all functions - quickly and easily accessed via the new intuitive menu button. The lightning-fast exchange of the heating element during operation will in future enable work with several tips in quick change. If a tip has to be replaced, this is done independently of the heating element - which saves enormous costs. The innovative 2-in-1 tray with rotatable plunger holder ensures a free choice between wet and dry cleaning. All stations of the WT-Line fit perfectly on top of each other, thus saving considerable space at the workplace.

Front-mounted power switch

The front-mounted power switch ensures easy operation at all times.

Multifunctional LC display

Products for the electronic industry



Unique LC display with detailed overview of all functions. Adjustable backlight. Power bar graph allows you to visually check the current power of the soldering station.

Comfortable menu button

The new menu button ensures maximum user-friendliness and easy navigation in the menu structure.

Space-saving

The WT 1 / WT 1H can be stacked on top of the WTHA 1 to ensure more space at the workstation.

2-in-1 WSR tray

The piston holder can be rotated 180°. The user can choose between wet and dry cleaning.

- Pokrywa obudowy może być używana jako dodatkowa półka
- Nowoczesna koncepcja obsługi
- Intuicyjna obsługa dzięki przejrzystej nawigacji po menu
- Zajmuje mało miejsca dzięki możliwości sztaplowania
- Graficzny wyświetlacz LC z podświetleniem tła
- Duża funkcjonalność i elastyczność - możliwość podłączenia wielu narzędzi
- Automatyczne odłączanie przy wykorzystaniu czujnika zużycia zamontowanego w narzędziu
- Funkcja blokady
- Połączenie wyrównawcze
- Kompatybilność z WT

numer pozycji	WL36829
Model	WT 1H
Linia modelowa	WT 1H
Producent	WELLER
Numer artykułu producenta	T0053435699N
Długość	149 mm
Szerokość	138 mm
Wysokość	101 mm
Długość w calach	5,87 in
Szerokość cala	5,43 in
Wysokość cale	3,98 in
Jednostka sprzedaży	1 sztuka
Jednostka zawartości	1 sztuka

Moc	150 W
Bezpiecznik	T2A
Napięcie	230 V
Zakres temperatur °C	50 – 550 °C
Zakres temperatur °F	150 – 999 °F
Dokładność temperaturowa °F	±17 °F
Stabilność temperaturowa °C	±2 °C
Stabilność temperaturowa °F	±4 °F
Liczba kanałów	1