WT 1010, cyfrowa 1-kanałowa stacja lutownicza, 95 W



This is soldering today
The detailed LC display provides an unprecedented overview of all functions, quickly and easily accessible via the new user-friendly menu button. The lightning-fast exchange of the heating element during operation makes it possible to work with several tips in quick succession. If a tip needs to be replaced, this is done independently of the heating element - which saves enormous costs.

Front-mounted power switch
The front-mounted power switch ensures easy operation at all times.

Multifunctional LC display
Unique LC display with detailed overview of all functions. Adjustable backlight. The power bar graph allows you to visually check the current power of the soldering station.

Convenient menu button
The new menu button ensures maximum user-friendliness and easy navigation in the menu structure.

Space-saving
The WT 1 / WT 1H can be stacked on top of the WTHA 1 to ensure more space at the workstation.

2-in-1 WSR tray
The plunger holder can be rotated 180°. The user can choose between wet and dry cleaning.
• WTP 90: Uniwersalna kolba lutownicza Hightech z grotem lutowniczym Power Response. Seria grotów lutowniczych XNT & THM (groty o dużej masie)
• Funkcja blokady
• Wyświetlacz: LCD / Podświetlenie tła
• Połączenie wyrównawcze
• Kompatybilność z WT

Numer artykułu.	**WL37223**
Model	WT 1010 Set
Linia modelowa	WT 1
Producent	WELLER
Numer artykułu producenta.	T0053436699N
Dane producenta GPSR	WELLER Tools GmbH Carl-Benz-Strasse 2 DE-74354 Besigheim www.weller-tools.com
Długość	149 mm
Szerokość	138 mm
Wysokość	101 mm
Zakres dostawy	1x 1-channel supply unit WT 1 1x WTP 90 soldering iron 1x soldering tip XNT A 1x change tool 1x WSR 200 safety rest 1x rubber rest 1x mains plug 1x instruction manual
Długość w calach	5,87 in
Szerokość w calach	5,43 in
Wysokość w calach	3,98 in
Jednostka sprzedaży	1 Zestaw
Jednostka treści	1 zestaw
Częstotliwość	50/60 Hz

Moc	95 W
Woltaż	230 V
Bezpiecznik	0,5 A
Zakres temperatur °C	50 – 450 °C
Zakres temperatur °F	150 – 850 °F
Dokładność temperatury °F	±17 °F
Dołączona(e) półka(i)	WSR 200
Dołączona/e końcówka/i lutownicza/e	XNT A
Dołączona jednostka sterująca	WT 1
Dołączona lutownica	WTP 90
Stacja (typ)	Stacja lutownicza
Stabilność temperatury °C	±2 °C
Stabilność temperatury °F	±4 °F
Zgodny z ESD	tak