

## Mini myjka wysokociśnieniowa

---



---

### Mini high-pressure cleaner

- Effective removal of persistent marks with "scouring agent jets"
- A mixture of conventional scouring agent and water can be processed in a ratio of approx. 1/2 to 1/5 in the built-in, fully swivelling tank
- Dust-free cleaning

#### Technical data:

- Liquid consumption: approx. 110 ml/min at 5 bar
- Viscosity range: 1 - 300 mm/sec. at 20° C
- Operating pressure: 2 - 8 bar
- Tank: 350 ml integrated, replaceable
- Air consumption: approx. 70 l/min at 6 bar
- Noise level: approx. 85 dB
- Pipe diameter: 7 mm
- Pipe length: 60 mm
- Pressure connector: 1/2 inch 7.2

---

Products for the electronic industry



- Pressure control integrated on the device
- Beam width: adjustable from approx. 1.5 mm to 3 mm
- Spray angle: approx. 15° - 20°

|                            |  |
|----------------------------|--|
| <b>Numer artykułu.</b>     | <b>WL41058</b>   |
| Model                      | LicoJet Rubber   |
| Producent                  | LICO-TEC   |
| Numer artykułu producenta. | 200102   |
| Dane producenta GPSR       | Lico-Tec GmbH<br>Lehmhäuserstr. 20<br>DE-94424 Arnstorf<br>www.lico-tec.de |
| Jednostka sprzedaży        | 1 sztuka   |
| Jednostka treści           | 1 sztuka   |
| W zestawie bateria         | nie  |

