Stacja lutownicza/rozlutownicza Nano, z AN115-A, NT115-A, 230 V



Discover the ultimate solution for soldering and reworking even the smallest SMDs. The 2-channel SMD rework station combines the outstanding features of the JBC Most Efficient Soldering System to offer you an unparalleled experience. JBC's intelligent thermal management significantly improves soldering quality. The station also has a sleep and hibernation mode that extends the life of the soldering tip by up to five times. An integrated tip cleaning system with wiper and brush ensures optimum working conditions at all times. The cartridge holder and JBC's exclusive cartridge exchanger further increase efficiency. Thanks to the RJ12 connector, connection to the JBC solder fume extraction system is easy. The station also offers comprehensive connectivity for data download, remote control for traceability and software updates. With the NT115 Nano handpiece and the flexible AN115 Nano Tweezers, which are compatible with the C115 tip series, you can significantly expand your repertoire of applications. This SMD rework station is the perfect choice for professionals who demand the highest standards of precision and efficiency.

• do elementów SMT
• niewielka odległość od grota do uchwytu zapewnia lepszą kontrolę, także podczas używania mikroskopu
• działa z kartuszami C115
• Moc szczytowa: 14 W na narzędzie

numer pozycji	**WL44267**
Model	NASE-2C
Linia modelowa	Premium Line
Producent	JBC
Numer artykułu producenta	NASE-2C
Długość	140 mm
Szerokość	170 mm
Wysokość	125 mm
Długość z opakowaniem	280 mm
Szerokość z opakowaniem	280 mm
Wysokość z opakowaniem	164 mm
Zakres dostawy	1 NAE Urządzenie sterujące 1 AN115-A Regulowana pęseta Nano 1 NT115-A Uchwyt Nano 1 C115101 Stożek Ø 0,1 1 C115103 Kształt stożka Ø 0,3 2 C115105 Kształt stożka, wygięty Ø 0,3 1 C115107 Kształt stożka Ø 0,8 1 C115112 Nóż 2,5x0,3 2 C115113 Dłuto 1x0,3 1 P-405 Pedał
Jednostka sprzedaży	1 sztuka
Jednostka zawartości	1 sztuka
Seria produktów	Premium Line
Wydajność grzewcza	14 W
Napięcie	230 V
Zakres temperatur °C	90 – 450 °C
Typ stacji	Stacja do odlutowania
Wskazanie cyfrowe	tak
zawarta jednostka sterująca	NAE
zawarty chwyt	AN115-A, NT115-A
Opór szczytowo-ziemny	<2 Ohm

Temperatura otoczenia	10 – 40 °C
Przyłącza	USB-A, USB-A, pedał (1 na narzędzie), połączenie wyrównawcze
Zgodność z ESD	tak