Stacja lutownicza Nano 2 Tool, 2x NT115-A, 230 V



The JBC NANE-2C 2-channel precision soldering station is an advanced soldering and desoldering station specifically designed for precision work on micro components such as 0201, 0402 and 01005 chips. Thanks to JBC's innovative technology, the NANE-2C offers outstanding performance and ease of use.
With an output of 2 × 14 W and a temperature range of 90-450°C, the NANE-2C enables fast and precise temperature control. The heating system integrated directly into the soldering tips ensures a heat-up time of just 2 seconds to 350°C and rapid temperature recovery, even during intensive soldering work. This reduces the risk of component damage and improves soldering quality.
The NANE-2C's 2-channel control unit enables the simultaneous operation of two NT115 Nano handpieces, which increases efficiency when working with multiple components. The capacitive multifunctional display with intuitive menu makes it easy to operate and adjust the settings. The station also has a USB interface for software updates and communication with a PC.
Another highlight is the sleep function, which automatically lowers the soldering tip

temperature to 180°C when the handpiece is put down. After a longer period of inactivity, the station switches to deep sleep mode, whereby the power supply to the handpiece is interrupted and the soldering tip cools down to room temperature. These functions help to extend the service life of the soldering tips.
The NANE-2C is compatible with the C115 soldering tip family and enables quick and easy soldering tip changes, even when hot. Optionally, one foot switch per channel can be connected to further simplify operation.
• do elementów SMT
• z dwoma uchwytami Nano NT115
• niewielka odległość od grota do uchwytu zapewnia lepszą kontrolę, także podczas używania mikroskopu
• działa z kartuszami C115
• Moc szczytowa: 14 W na narzędzie

Numer artykułu.	**WL44268**
Model	NANE-2C
Linia modelowa	Premium Line
Producent	JBC
Numer artykułu producenta.	NANE-2C
Dane producenta GPSR	JBC Soldering SL Ramón y Cajal 3 ES-08750 Molins De Rei www.jbctools.com
Długość z opakowaniem	280 mm
Szerokość z opakowaniem	280 mm
Wysokość z opakowaniem	164 mm
Zakres dostawy	Moduł podwójnego zasilania NA 2 x kolba lutownicza Nano NT115-A Groty lutownicze C115101, C115103, C115105, C115107, C115112, C115113
Jednostka sprzedaży	1 sztuka
Jednostka treści	1 sztuka
Seria produktów	Premium Line
Moc grzewcza	14 W
Moc	14 W
Woltaż	230 V
Napięcie	230 V
Zakres temperatur °C	90 – 450 °C
Dołączona jednostka sterująca	NAE

Dołączona rękojeść	NT115-A
Stacja (typ)	Stacja lutownicza
Rezystancja szczytowa do ziemi	<2 Ohm
Temperatura otoczenia	10 – 50 °C
Wartości połączenia	USB-A, USB-A, pedał (1 pro Tool), połączenie wyrównawcze, robot RS-232
Zgodny z ESD	tak